




9F, JINOUK BLDG. , 180-2, DANSSAN-DONG 2-GA, YEONGDEUNGPO-GU, SEOUL, KOREA

TYPICAL PROPERTIES OF SSP RESIN (COPOLYMER)

GRADE 80. 874-C80

PROPERTY	UNIT	VALUE	TEST METHOD
INTRINSIC VISCOSITY	dl /gr	0.80 + 0.02	UPILLARY VISCO/ETER
GLASS TRANSITION POINT	"C	246.0 + 2.0	DSC
CARBOXYL END GROUP	meq/kg	30 MAX	AUTO TITRATION
ACETALOEMIDE	ppc	1.0 MAX	SAS C/JR01/ATOGRAPH
MOISTURE CONTENT	%	0.2 MAX	THERMAL ANALYZER
DENSITY	gr/cu'	1.39 10.01	PMI A.G.P
COLOR		80.0 MIlt	HUFFTER Lab
		0.5 MCX	HUFFTER Lab
		1.0 MCX	HUNTER Lab
THICKNESS OF CHIP	ea/gr	65.0 5.0	

PACKING

1. IN CASE OF CONTAINER

(T) 1,000 KGS NET POLYPROPYLENE BAG, 2 BAGS ON ONE PALLET,
20,000 KGS/20' FCL

@ 1,050 KGS DIET POLYPROPYLENE BAG, 2 BAGS ON ONE PALLET,
21,000 KGS/20' FCL

@ 1,100 KGS NET POLYPROPYLENE BAG, 2 BAGS ON ONE PALLET,
22,000 KGS/20' FCL

2. SEA-BULK LINER SHIPMENT

AROUND 20,000 - 22,000 KGS/20' FCL