



TECHNICAL SPECIFICATION

CR-8816

CR8816 bottle-grade PET resin is applicable to packing bottles for drinking water such as pure water, mineral water and distilled water etc. It's also widely used for sheet extrusion. The product is good in processing performance, low in processing temperature, wide in processing allowance, good in product transparency and low in A.A and heavy metal concentration. It can maintain the respective taste of pure water, natural mineral water and distilled water.

CHARACTERISTICS UNIT VALUE **TEST METHOD TEST EQUIPMENT** 0.81+/-0.02 I.V. dg/g ASTM D5225 VISCOTEK Y501 AGILENT AA CONTENT mg/kg ≤1.0 WN-B010-9013E HEADSPACE ≤1.0 COLOR - bWN-B010-7136E X-RITE COLOR-L ≥80.0 COOH CONTENT mol/t ≤35 WN-B010-7013E METTLER DL50 °C MELTING POINT ≥240 WN-B010-7089E TA Q10 SIEVE ANALYSIS POWDER ≤100 GB17931-2003 mg/kg (RETSCH COMPANY) WATER CONTENT wt% ≤0.2 GB17931-2003 ASH CONTENT % ≤0.08 GB17931-2003

Packing situation: 1.1MT jumbo bag/20 bags in one 20' container

