PETResinGlobal

Technical Data Sheet

Manufacturer:

Sichuan Hanjiang New Material Co.,Ltd.

Product:

Polyester Chips for Bottle Grade

Grade:

HJ-666

Application:

FOR VACUUM BLOOD COLLECTION TUBES

Specifications:

NO.	ITEM	Property	TEST METHOD	UNIT	RANGE
1	I/V	Intrinsic Viscosity	GB17931	dl/g	0.63±0.015
			ASTM D4603		0.61±0.015
2	MELTING	Melting Point	GB17931	℃	246±2
3	COOH	Carboxyl End Group Content	GB17931	mol/t	≤40
4	COLOR	Colour b-value	GB17931	NA	≤2.0
		Colour L-value	GB17931	NA	≥75
5	DEG	Diethylene Glycol Content	GB17931	wt%	1.3±0.2
6	MOISTURE	Moisture	GB17931	wt%	≤0.40
7	ASH	Ash	GB17931	%	≤0.06
8	DUST	Powder	GB17931	mg/kg	≤100

Disclaimer: This document is for information purposes only. Customers are responsible for testing and confirming the suitability of this product in their application. To the extent permitted by law, no warranty as to merchantability or fitness of purpose, expressed or implied, is made.

GLOBAL OFFICES

USA
2106 House Ave, Suite 712,
Cheyenne, Wyoming 82001, USA

SINGAPORE
20 Collyer Quay, #09-01,
Singapore 049319

UAE
Shams Business Center, Al Messaned,
Sharjah, UAE

PAKISTAN
T1 Horizon Tower, Com 2/6, Khayaban
-e-Saadi, Block 3 Clifton, Karachi, Pakistan

www.petresinglobal.com

A Division Of Trimline Polymers

sales@petresinglobal.com +971-589-062082