

Technical Data Sheet

Manufacturer:

Reliance Industries Limited

Product:

Polyethylene Terephthalate

Grade:

Relpet® H7761

Application:

Hot fill applications

Specifications:

Typical properties of Relpet® H7761 are as follows:

Sl. No.	Property	Unit	Value	Range	Equipment / Test method
1	Intrinsic * Viscosity (IV)	dl/g	0.76	± 0.02	Ubbelohde Viscometer / ASTM D 4603
2	Acetaldehyde (AA)	ppm	1.0	Max.	Head Space & Gas Chromatography / ASTM F2013
3	Colour b*	CIE	0 to -3	-	Hunterlab / ASTM D6290
4	Crystallinity	%	50	Min.	Density Gradient Column / ASTM - D1505 / D 792
5	Fines	ppm	80	Max	Sieve Shaker using ASTM-16 mesh / QAF-PCL-3.407
6	Chips/gm	No.	68	± 5	Weighment method/ QAF-PCL-3.408
7	Melting Point	C	252	± 3	DSC QAF-PCL 3.416

Disclaimer: This document is for information purposes only. Customers are responsible for testing and confirming the suitability of this product in their application. To the extent permitted by law, no warranty as to merchantability or fitness of purpose, expressed or implied, is made.

GLOBAL OFFICES

USA

2106 House Ave, Suite 712,
Cheyenne, Wyoming 82001, USA

SINGAPORE

20 Collyer Quay, #09-01,
Singapore 049319

UAE

Shams Business Center, Al Messaned,
Sharjah, UAE

PAKISTAN

T1 Horizon Tower, Com 2/6, Khayaban
-e-Saadi, Block 3 Clifton, Karachi, Pakistan

Technical Data Sheet

Product Description and Applications:

Relpet® H7761 is bottle grade PET resin manufactured using Du Pont's technology.

Relpet® H7761 is specially formulate for hot filling of products like Juices, Ice Tea, Isotonic drinks etc.

Features:

Relpet® H7761 is engineered to provide:

- Good process ability
- Higher neck and body crystallinity
- Excellent clarity and gloss
- Low moisture when packed (<0.2%)

Certifications:

Relpet® H7761 resin is considered safe for food-packaging applications based on compliance with FDA regulation 21 CFR Section 177.1630 & other similar food contact safety regulations. Manufacturing facilities and system meet ISO 22000 standard.

Relpet® is registered trademark of Reliance Industries Limited.

PET manufacturing test facility/methods are accredited as per National Accreditation Board for Testing & Calibration Laboratories, India.

Manufacturer Notice:

The information and data presented herein is true and accurate to the best of our knowledge. No warranty or guarantee expressed or implied is made regarding performance or otherwise. This information and data may not be considered as a suggestion to use our products without taking into account existing patents, or legal provisions or regulations, whether national or local.

The user of any information and/or data is advised to obtain the latest details from any of the offices of the company or its authorized agent, as the information and/or data is subject to change based on the research and development work undertaken by the company.

Disclaimer: This document is for information purposes only. Customers are responsible for testing and confirming the suitability of this product in their application. To the extent permitted by law, no warranty as to merchantability or fitness of purpose, expressed or implied, is made.

GLOBAL OFFICES

USA

2106 House Ave, Suite 712,
Cheyenne, Wyoming 82001, USA

SINGAPORE

20 Collyer Quay, #09-01,
Singapore 049319

UAE

Shams Business Center, Al Messaned,
Sharjah, UAE

PAKISTAN

T1 Horizon Tower, Com 2/6, Khayaban
-e-Saadi, Block 3 Clifton, Karachi, Pakistan